

Author Index of Volume A63

- Ansari, F., 177
- Bao, M., 1, 19, 217
- Beetschwinger, U., 229
- Benoit, D., 251
- Bergveld, P., 97, 163
- Buchanan, R.C., 33
- Cattan, E., 91
- Chahoud, M., 141
- Chao, L.-P., 105
- Chen, H., 19, 217
- Chen, K.-T., 105
- Cheng, Y.C., 147, 223
- Choi, W.K., 243
- Chong, C.W., 243
- Cunningham, M.J., 125, 135
- Damjanovic, D., 153
- Delannay, G., 7
- Devos, F., 205
- Estève, D., 183
- Fan, S., 169
- Fenniri, H., 7
- Fisher, N.E., 27, 119
- Fox, G.R., 153
- Gaub, H.E., 47
- Grattan, K.T.V., 85, 113, 197
- Hardcastle, B.M., 61
- Hofmann, U.G., 47
- Hök, B., 69
- Hu, Y.L., 85
- Huang, M.Q., 223
- Jaber, B., 91
- Jackson, D.A., 27, 119
- Jakšić, A., 129
- Jenkins, D.F.L., 125, 135
- Khalid, M.A.Hj., 125
- Lai, P.T., 147, 223
- Lawes, R.A., 61
- Lee, M.H., 169
- Li, B., 147
- Li, G.Q., 223
- Li, X., 1, 217
- Li, Z., 209
- Linde, H., 251
- Liu, B.Y., 147
- Liu, G., 169
- Liu, L., 209
- Ludden, B.P., 15
- Meggitt, B.T., 85
- Meijerink, M.G.H., 163
- Moineau, A., 7
- Ni, Y., 205
- Ning, Y.N., 113
- Olthuis, W., 97, 163
- Owrick, J.C., 47
- Palmer, A.W., 85, 113
- Parak, W.J., 47
- Pechstein, T., 191
- Pedersen, M., 97, 163
- Pejović, M., 129
- Reid, D.J.C., 15
- Remiens, D., 91, 135
- Reuben, R.L., 229
- Ristić, G., 129
- Robertson, P.A., 15
- Romare, D., 197
- Rossi, C., 183
- Rule, J., 15
- Sabry-Rizk, M., 197
- Scheid, E., 183
- Schachetzki, A., 141
- Shen, S., 1, 19, 217
- Smith, L., 69
- Sorge, S., 191
- Strandman, C., 69
- Sundeen, J.E., 33
- Syms, R.R.A., 61
- Tenez, L., 69
- Thierry, B., 91
- Thong, J.T.L., 243
- Tronc, P., 91
- Velu, G., 135
- Wajid, A., 41
- Wang, C., 205
- Wehmann, H.-H., 141
- Whiting, C., 251
- Woolsey, G.A., 27, 119
- Yang, S.J., 229
- Yuan, L., 177
- Zeng, S.H., 223
- Zhang, W., 113
- Zhang, Z.Y., 85
- Zheng, X.R., 147
- Zhu, H., 19
- Zou, Q., 209

Subject Index of Volume A63

- Accelerometers**
a piezoresistive accelerometer with a novel vertical beam structure, 19
- Acoustic detection**
Bragg grating in a two-mode optical fibre for sensing applications, 15
- Adaptive filtering**
evaluation of different adaptive filtering techniques applied to white-light interferometric sensor systems, 197
- Anisotropic etching**
a production process of silicon sensor elements for a fibre-optic pressure sensor, 69
anisotropic-etching simulation of InP and Si, 141
- Beams**
finite-element modelling and simulation on frequency characteristics of the silicon beam resonator attached to an E-type round diaphragm for measuring the concentrated force, 169
- Bulk-glass current sensors**
tuning a bulk-glass optical current sensor by controlling conditions external to its reflecting surfaces, 27
- Faraday current sensors and the significance of subtended angles, 119**
- Bulk micromachining**
bulk micromachined silicon comb-drive electrostatic actuators with diode isolation, 61
- Capacitance**
study on linearization of silicon capacitive pressure sensors, 1
- Capacitive sensors**
an IC-compatible polyimide pressure sensor with capacitive readout, 163
- Ceramics**
characterization of ferroelectric and piezoelectric properties of lead titanate thin films deposited on Si by sputtering, 91
- Cermet films**
electrical properties of nickel–zirconia cermet films for temperature- and flow-sensor applications, 33
- Comb-drive electrostatic actuators**
bulk micromachined silicon comb-drive electrostatic actuators with diode isolation, 61
- Composite films**
electrical properties of nickel–zirconia cermet films for temperature- and flow-sensor applications, 33
- Condenser microphones**
theoretical and experimental studies of single-chip-processed miniature silicon condenser microphone with corrugated diaphragm, 209
- Conduction percolation**
electrical properties of nickel–zirconia cermet films for temperature- and flow-sensor applications, 33
- Corrugated diaphragms**
theoretical and experimental studies of single-chip-processed miniature silicon condenser microphone with corrugated diaphragm, 209
- CVD oxide**
PMOS dosimetric transistors with two-layer gate oxide, 129
- Decay-time thermometry**
ruby-based decay-time thermometry: effect of probe size on extended measurement range (77–800 K), 85
- Deconvolution**
the use of some iterative deconvolution algorithms to improve the spatial resolution of a flat magnetic sensor, 7
- Dielectric membranes**
theoretical and experimental study of silicon micromachined microheater with dielectric stacked membranes, 183
- Differential sensors**
an IC-compatible polyimide pressure sensor with capacitive readout, 163
- Diode isolation**
bulk micromachined silicon comb-drive electrostatic actuators with diode isolation, 61
- Electrostatic actuation**
cantilever vibration control by electrostatic actuation for magnetic force microscopy, 125
- Etch characteristics**
etch characteristics of various materials in ethanolaniline etchants, 251
- Etching parameters**
TMAH etching of silicon and the interaction of etching parameters, 243
- Etching simulation**
anisotropic-etching simulation of InP and Si, 141
- Ethanolaniline etchants**
etch characteristics of various materials in ethanolaniline etchants, 251
- E-type round diaphragms**
finite-element modelling and simulation on frequency characteristics of the silicon beam resonator attached to an E-type round diaphragm for measuring the concentrated force, 169
- Fading**
PMOS dosimetric transistors with two-layer gate oxide, 129
- Faraday current sensors**
Faraday current sensors and the significance of subtended angles, 119
- Ferroelectric properties**
characterization of ferroelectric and piezoelectric properties of lead titanate thin films deposited on Si by sputtering, 91
- Fiber optics**
white-light interferometric fiber-optic distributed strain-sensing system, 177
- Fiber-optic thermometers**
ruby-based decay-time thermometry: effect of probe size on extended measurement range (77–800 K), 85
- Fibre Bragg gratings**
Bragg grating in a two-mode optical fibre for sensing applications, 15
- Finite-element method**
finite-element modelling and simulation on frequency characteristics of the silicon beam resonator attached to an E-type round diaphragm for measuring the concentrated force, 169

- Flow sensors
 - electrical properties of nickel–zirconia cermet films for temperature- and flow-sensor applications, 33
- Fluorescence lifetime
 - ruby-based decay-time thermometry: effect of probe size on extended measurement range (77–800 K), 85
- Force
 - finite-element modelling and simulation on frequency characteristics of the silicon beam resonator attached to an E-type round diaphragm for measuring the concentrated force, 169
- Force sensitivity evaluation
 - shape optimal design and force sensitivity evaluation of six-axis force sensors, 105
- Force sensors
 - shape optimal design and force sensitivity evaluation of six-axis force sensors, 105
- Friction
 - frictional study of micromotor bearings, 229
- Gas chromatography
 - fully integrated thermal conductivity sensor for gas chromatography without dead volume, 191
- Gas sensors
 - fully integrated thermal conductivity sensor for gas chromatography without dead volume, 191
- Guide-wire fibre-optic pressure sensors
 - a production process of silicon sensor elements for a fibre-optic pressure sensor, 69
- Humidity sensitivity
 - photo-, thermal and humidity sensitivity characteristics of $\text{Sr}_{1-x}\text{La}_x\text{TiO}_3$ film on SiO_2/Si substrate, 223
- IC-compatible sensors
 - a silicon condenser microphone with polyimide diaphragm and back-plate, 97
- Indium phosphide
 - anisotropic-etching simulation of InP and Si, 141
- Integrated sensors
 - an integrated PVDF ultrasonic sensor with improved sensitivity using polyimide, 147
 - an IC-compatible polyimide pressure sensor with capacitive readout, 163
- Interface traps
 - PMOS dosimetric transistors with two-layer gate oxide, 129
- Iterative algorithms
 - the use of some iterative deconvolution algorithms to improve the spatial resolution of a flat magnetic sensor, 7
- Lateral acceleration
 - a piezoresistive accelerometer with a novel vertical beam structure, 19
- Lateral resolution
 - lateral resolution of light-addressable potentiometric sensors: an experimental and theoretical investigation, 47
- Lead titanate
 - characterization of ferroelectric and piezoelectric properties of lead titanate thin films deposited on Si by sputtering, 91
- Light-addressable potentiometric sensors (LAPs)
 - lateral resolution of light-addressable potentiometric sensors: an experimental and theoretical investigation, 47
- Light-pulse detectors
 - a cumulative differential light-pulse detector using source-coupled MOS current switches, 205
- Linearity
 - study on linearization of silicon capacitive pressure sensors, 1
- Magnetic force microscopy
 - cantilever vibration control by electrostatic actuation for magnetic force microscopy, 125
- Maskless etching
 - a novel micromachining technology for multilevel structures of silicon, 217
- Microactuators
 - the use of sputtered ZnO piezoelectric thin films as broad-band microactuators, 135
- Microheaters
 - theoretical and experimental study of silicon micromachined microheater with dielectric stacked membranes, 183
- Micromachining
 - a piezoresistive accelerometer with a novel vertical beam structure, 19
 - a novel micromachining technology for multilevel structures of silicon, 217
- Micromotor bearings
 - frictional study of micromotor bearings, 229
- Microsensors
 - finite-element modelling and simulation on frequency characteristics of the silicon beam resonator attached to an E-type round diaphragm for measuring the concentrated force, 169
- MOS current switches
 - a cumulative differential light-pulse detector using source-coupled MOS current switches, 205
- Optical current-measurement systems
 - analysis of the effect of vibration-induced noise in different fibre leads used in an optical current-measurement system, 113
- Optical current sensors
 - Faraday current sensors and the significance of subtended angles, 119
- Optical fibres
 - analysis of the effect of vibration-induced noise in different fibre leads used in an optical current-measurement system, 113
- Optical phase modulator
 - electrical characterization of sputter-deposited ZnO coatings on optical fibers, 153
- Optimal design
 - shape optimal design and force sensitivity evaluation of six-axis force sensors, 105
- Oxide trapped charge
 - PMOS dosimetric transistors with two-layer gate oxide, 129
- Photosensitivity
 - photo-, thermal and humidity sensitivity characteristics of $\text{Sr}_{1-x}\text{La}_x\text{TiO}_3$ film on SiO_2/Si substrate, 223
- Piezoelectric optical-fiber coatings
 - electrical characterization of sputter-deposited ZnO coatings on optical fibers, 153
- Piezoelectric properties
 - characterization of ferroelectric and piezoelectric properties of lead titanate thin films deposited on Si by sputtering, 91
- Piezoelectric thin films
 - the use of sputtered ZnO piezoelectric thin films as broad-band microactuators, 135
- electrical characterization of sputter-deposited ZnO coatings on optical fibers, 153
- {100} Planes
 - a production process of silicon sensor elements for a fibre-optic pressure sensor, 69
- PMOS dosimeters
 - PMOS dosimetric transistors with two-layer gate oxide, 129
- Polyimide
 - a silicon condenser microphone with polyimide diaphragm and back-plate, 97
 - an integrated PVDF ultrasonic sensor with improved sensitivity using polyimide, 147

- an IC-compatible polyimide pressure sensor with capacitive readout, 163
- Potassium hydroxide
 - a production process of silicon sensor elements for a fibre-optic pressure sensor, 69
- Pressure sensors
 - study on linearization of silicon capacitive pressure sensors, 1
 - an IC-compatible polyimide pressure sensor with capacitive readout, 163
- Quartz-crystal microbalances
 - on the accuracy of the quartz-crystal microbalance (QCM) in thin-film depositions, 41
- Radial resonance
 - electrical characterization of sputter-deposited ZnO coatings on optical fibers, 153
- Reactive sputtering
 - electrical characterization of sputter-deposited ZnO coatings on optical fibers, 153
- Restoration of sensor images
 - the use of some iterative deconvolution algorithms to improve the spatial resolution of a flat magnetic sensor, 7
- Ruby
 - ruby-based decay-time thermometry: effect of probe size on extended measurement range (77-800 K), 85
- Sensitivity
 - PMOS dosimetric transistors with two-layer gate oxide, 129
- Silicon
 - study on linearization of silicon capacitive pressure sensors, 1
 - bulk micromachined silicon comb-drive electrostatic actuators with diode isolation, 61
 - characterization of ferroelectric and piezoelectric properties of lead titanate thin films deposited on Si by sputtering, 91
 - anisotropic-etching simulation of InP and Si, 141
 - TMAH etching of silicon and the interaction of etching parameters, 243
- Silicon condenser microphones
 - a silicon condenser microphone with polyimide diaphragm and back-plate, 97
- Silicon etch
 - a novel micromachining technology for multilevel structures of silicon, 217
- Single-chip fabrication
 - theoretical and experimental studies of single-chip-processed miniature silicon condenser microphone with corrugated diaphragm, 209
- $\text{Sr}_{1-x}\text{La}_x\text{TiO}_3$ thin films
 - photo-, thermal and humidity sensitivity characteristics of $\text{Sr}_{1-x}\text{La}_x\text{TiO}_3$ film on SiO_2/Si substrate, 223
- Strain gages
 - shape optimal design and force sensitivity evaluation of six-axis force sensors, 105
- Strain sensors
 - white-light interferometric fiber-optic distributed strain-sensing system, 177
- Subtended angles
 - Faraday current sensors and the significance of subtended angles, 119
- Temperature coefficient of resistance
 - electrical properties of nickel-zirconia cermet films for temperature- and flow-sensor applications, 33
- Tetramethylammonium hydroxide (TMAH)
 - TMAH etching of silicon and the interaction of etching parameters, 243
- Thermal conductivity detectors
 - fully integrated thermal conductivity sensor for gas chromatography without dead volume, 191
- Thermal optimization
 - theoretical and experimental study of silicon micromachined micro-heater with dielectric stacked membranes, 183
- Thermal sensitivity
 - photo-, thermal and humidity sensitivity characteristics of $\text{Sr}_{1-x}\text{La}_x\text{TiO}_3$ film on SiO_2/Si substrate, 223
- Thin films
 - on the accuracy of the quartz-crystal microbalance (QCM) in thin-film depositions, 41
- Tuning
 - tuning a bulk-glass optical current sensor by controlling conditions external to its reflecting surfaces, 27
- Ultrasonic transducers
 - an integrated PVDF ultrasonic sensor with improved sensitivity using polyimide, 147
- Vibration control
 - cantilever vibration control by electrostatic actuation for magnetic force microscopy, 125
- Vibration-induced noise
 - analysis of the effect of vibration-induced noise in different fibre leads used in an optical current-measurement system, 113
- White-light interferometry
 - white-light interferometric fiber-optic distributed strain-sensing system, 177
 - evaluation of different adaptive filtering techniques applied to white-light interferometric sensor systems, 197
- Zinc oxide
 - the use of sputtered ZnO piezoelectric thin films as broad-band microactuators, 135
 - electrical characterization of sputter-deposited ZnO coatings on optical fibers, 153
- Z-match technique
 - on the accuracy of the quartz-crystal microbalance (QCM) in thin-film depositions, 41



1